

Safety data sheet

Safe Work Australia - Code of Practice



Magnesium ribbon $\geq 99,5\%$

article number: **4468**
Version: **GHS 3.0 en**
Replaces version of: 2020-10-22
Version: (GHS 2)

date of compilation: 2017-01-23
Revision: 2021-08-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Magnesium ribbon $\geq 99,5\%$
Article number	4468
Registration number (REACH)	It is not required to list the identified uses because the substance is not subject to registration according to REACH (< 1 t/a)
Index No	012-002-00-9
EC number	231-104-6
CAS number	7439-95-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: laboratory chemical
laboratory and analytical use

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/ city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

Emergency information service

Poison Centre Munich: +49/(0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet

Safe Work Australia - Code of Practice



Magnesium ribbon $\geq 99,5\%$

article number: **4468**

Classification acc. to GHS

Classification acc. to GHS			
Section	Hazard class	Hazard class and category	Hazard statement
2.7	flammable solid	(Flam. Sol. 2)	H228
2.12	substance and mixture which, in contact with water, emits flammable gas	(Water-react. 2)	H261

2.2 Label elements

Labelling GHS

Signal word

Danger

Pictograms

GHS02



Hazard statements

H228 Flammable solid
H261 In contact with water releases flammable gases

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P231+P232 Handle and store contents under inert gas. Protect from moisture.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - response

P302+P335+P334 IF ON SKIN: Brush off loose particles from skin. Immerse in cool water or wrap in wet bandages.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction.

Precautionary statements - storage

P402+P404 Store in a dry place. Store in a closed container.

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



Safety data sheet

Safe Work Australia - Code of Practice



Magnesium ribbon $\geq 99,5\%$

article number: **4468**

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Magnesium
Index No	012-002-00-9
EC number	231-104-6
CAS number	7439-95-4
Molecular formula	Mg
Molar mass	24.31 g/mol

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Magnesium ribbon $\geq 99,5\%$

article number: **4468**

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings
water spray, foam, dry extinguishing powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

None.

5.3 Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Eliminate all ignition sources if safe to do so. Control of dust. Do not breathe dust.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures are necessary.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place. Do not allow contact with water.

Incompatible substances or mixtures

Do not allow contact with water. Observe hints for combined storage.

Magnesium ribbon ≥99,5 %

article number: **4468**

Consideration of other advice

- **Ventilation requirements**

Use local and general ventilation.

- **Specific designs for storage rooms or vessels**

Recommended storage temperature: 15 – 25 °C.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Data are not available.

Relevant DNELs/DMELs/PNECs and other threshold levels

- **human health values**

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	10 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

- **environmental values**

Endpoint	Threshold level	Environmental compartment	Exposure time
PNEC	0.41 mg/l	freshwater	short-term (single instance)
PNEC	0.41 mg/l	marine water	short-term (single instance)
PNEC	10.8 mg/l	sewage treatment plant (STP)	short-term (single instance)
PNEC	268 mg/kg	freshwater sediment	short-term (single instance)
PNEC	268 mg/kg	marine sediment	short-term (single instance)
PNEC	268 mg/kg	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



Magnesium ribbon $\geq 99,5\%$

article number: **4468**

• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P1 (filters at least 80 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	solid
Colour	silver grey
Odour	odourless
Odour threshold	no data available

Other physical and chemical parameters

pH (value)	this information is not available
Melting point/freezing point	650 °C at 1,013 hPa
Initial boiling point and boiling range	1,107 °C at 1,013 hPa
Flash point	not applicable
Evaporation rate	no data available
Flammability (solid, gas)	Flammable solid in accordance with GHS criteria

Magnesium ribbon $\geq 99,5\%$

article number: **4468**

Explosive limits

• lower explosion limit (LEL)	this information is not available
• upper explosion limit (UEL)	this information is not available
Explosion limits of dust clouds	these information are not available
Vapour pressure	3.72 hPa at 650 °C
Density	1.75 g/cm ³ at 20 °C
Vapour density	this information is not available
Bulk density	300 – 400 kg/m ³
Relative density	this information is not available

Solubility(ies)

Water solubility 0.007 g/l at 21 °C

Partition coefficient

n-octanol/water (log KOW) this information is not available

Auto-ignition temperature >450 °C

Decomposition temperature no data available

Viscosity not relevant (solid matter)

Explosive properties Shall not be classified as explosive.

Oxidising properties none

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from moisture.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Magnesium ribbon ≥99,5 %

article number: **4468**

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Shall not be classified as acutely toxic.

Exposure route	Endpoint	Value	Species	Source
oral	LD50	>2,000 mg/kg	rat	ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant

- **Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

- **Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

- **If swallowed**

data are not available

- **If in eyes**

data are not available

- **If inhaled**

data are not available

- **If on skin**

data are not available

Other information

None

Magnesium ribbon ≥99,5 %

article number: **4468**

SECTION 12: Ecological information

12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	541 mg/l	fish	ECHA	96 h
ErC50	>12 mg/l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	125 mg/l	aquatic invertebrates	ECHA	21 d
growth (EbCx) 16%	82 mg/l	aquatic invertebrates	ECHA	21 d

12.2 Process of degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Safety data sheet

Safe Work Australia - Code of Practice




Magnesium ribbon $\geq 99,5\%$

article number: **4468**

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number	1869
14.2	UN proper shipping name	MAGNESIUM
	Hazardous ingredients	Magnesium
14.3	Transport hazard class(es)	
	Class	4.1 (flammable solids)
14.4	Packing group	III (substance presenting low danger)
14.5	Environmental hazards	none (non-environmentally hazardous acc. to the dangerous goods regulations)

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number	1869
Proper shipping name	MAGNESIUM
Particulars in the transport document	UN1869, MAGNESIUM, 4.1, III, (E)
Class	4.1
Classification code	F3
Packing group	III
Danger label(s)	4.1



Special provisions (SP)	59
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 kg
Transport category (TC)	3
Tunnel restriction code (TRC)	E
Hazard identification No	40
Emergency Action Code	1Z

Safety data sheet

Safe Work Australia - Code of Practice



Magnesium ribbon $\geq 99,5\%$

article number: **4468**

• International Maritime Dangerous Goods Code (IMDG)

UN number	1869
Proper shipping name	MAGNESIUM
Particulars in the shipper's declaration	UN1869, MAGNESIUM, 4.1, III
Class	4.1
Marine pollutant	-
Packing group	III
Danger label(s)	4.1



Special provisions (SP)	59, 920
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 kg
EmS	F-G, S-G
Stowage category	A

• International Civil Aviation Organization (ICAO-IATA/DGR)

UN number	1869
Proper shipping name	Magnesium
Particulars in the shipper's declaration	UN1869, Magnesium, 4.1, III
Class	4.1
Packing group	III
Danger label(s)	4.1



Special provisions (SP)	A15
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National inventories

Substance is listed in the following national inventories:

Magnesium ribbon ≥99,5 %

article number: **4468**

Country	National inventories	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CMR	Carcinogenic, Mutagenic or toxic for Reproduction

Magnesium ribbon $\geq 99,5\%$

article number: **4468**

Abbr.	Descriptions of used abbreviations
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	\equiv EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
vPvB	very Persistent and very Bioaccumulative

Key literature references and sources for data

- UN Recommendations on the Transport of Dangerous Good
- Dangerous Goods Regulations (DGR) for the air transport (IATA)
- International Maritime Dangerous Goods Code (IMDG)

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H228	flammable solid
H261	in contact with water releases flammable gases

Safety data sheet

Safe Work Australia - Code of Practice



Magnesium ribbon $\geq 99,5$ %

article number: **4468**

Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.